MARINE

Marine Warehouse

2330 NW 102 Avenue, Suite 1 Doral, FL 33172

USA

Tel: (305) 635-0776 spectra@marinewarehouse.net

CAPE HORN EXTREME CH-330 WATERMAKER 330GPD/14GPH - 1300 LPD/54LPH



The Cape Horn Extreme system includes:

Seawater strainer

Pre-filter housing with 5 micron filter element

2 feed water pumps with heat sink and cooling fans

Composite Spectra High Pressure Pump

One 40 inch high rejection/high yield spiral wound reverse osmosis membrane

Spectra free flow ultra efficient high pressure vessel assembly

Spectra Pump and membrane housing mounted and plumbed together with mounting brackets

Accumulator

Manual fresh water flush system with 3-way valve for cleaning and flushing procedures

Charcoal filter and housing

25 ft. 3/4 suction hose

25 ft. 5/8 inch reinforced sea water hose

25 ft. LP product tubing

Instrument panel with feed water pressure gauge and product flow meter

Hand-held salinity monitor

All required tube fittings and hose clamps

One SC-1 storage chemical

Complete installation and operation manual

Warranty registration card



Available systems:

CH-330-12 Cape Horn Extreme System 12 VDC (One 40" Membrane)

CH-330-24 Cape Horn Extreme System 24 VDC (One 40" Membrane)

CH-330-12-S Cape Horn Extreme System 12 VDC (Two Short 20" Membranes)

CH-330-24-S Cape Horn Extreme System 24 VDC (Two Short 20" Membranes)

Shipping Details:

Shipping Weight: 78

• Shipping Dimensions: 47" x 23" x 18"

• Country Of Origin: USA

Class: 150

Tariff Code: 8421210000Ships By: FX-Gr/Expr, LCL, LTL

• Shipping FedEx Worldwide at 65% discount

Optional Equipment:

Z-Ion Protection System

• Dedicated 3/4" thru hull (bronze or marelon)

Y-valve 1/4" for 2nd Tank (sku: PL-VLV-3W1/4)

Y-Valve Connectors (sku: PL-MTS-1/4x1/4J)

• Extra Product Tubing (sku: PL-NLT-1/4LP)

Cruise Kit "A" (sku: KIT-BCK-A)



SPECTRA CAPE HORN EXTREME 330 WATERMAKER

PRODUCT SPECIFICATIONS

Production / Day 330 gal (1249 l) Production / Hour 15 gal (56 l)

12v DC 19A / 24v DC 10A Power Requirement

16 Watts/1 gal 4.2 Watts/1 liter

Weight 65 lbs (29 kg)

Pre Filters 2.5"x10" pleated polyester 5 micron

Controls Analog controls

Dedicated thruhull, dry and well ventilated area not to exceed Installation Requirements

110F/37C

40" x 2.5" High rejection spiral Membranes

wound polyamide

Pump and Motor Shurflo diaphragm pump

99.2% Salt Rejection

Max 110F/37C Min 36F/2C Temperature Range

Baseline Conditions 33,000 PPM feed water at 77F/25C

pH Range 3-11 (typical seawater pH is 8)

Chlorine Tolerance O PPM

Spectra standard warranty Warranty

Shipping Weight 95 lbs (43 kg) 47"x23"x18"

Shipping Dimensions 120cm x 59cm x 46cm





FACTS

The The Cape Horn Extreme continues to be the choice for serious offshore racing campaigns like the Volvo Ocean Race and Clipper Challenge round-the-world yachts. The Cape Horn Extreme is reliable and durable, with its diaphragm feed pumps in parallel, it can be run on a single pump for high efficiency or two pumps for high output. The system uses rugged mechanical controls and gauges and is perfect for the hands-on racer or cruiser.

FEATURES


- Redundant dual feed pumps for maximum reliability
- Simple analog control panel
- Compact modular design
- Spectra's unique Clark Pump for efficiency and reliability
- High and low speed operation for customizable power management and output volume
- Low power consumption, can be run on batteries, solar, or wind power
- Commercial grade diaphragm pumps with run dry protection
- System includes installation kit, handheld water quality tester, and product sample valve
- Z±ION Compatible



SPECTRA CAPE HORN EXTREME 330 WATERMAKER



Feed Pump Module Depth 4.5" / 11.4 cm



Secondary Feed Pump Module Depth 6" / 5.2 cm



44" / 112 cm High Pressure Clark Pump and Membrane Depth 12" / 30.5 cm

Katadyn reserves the right to modify products

Katadyn Desalination

Spectra Watermakers 20 Mariposa Road San Rafael, CA 94901

TEL: 1-415-526-2780 FAX: 1-414-526-2787 E-MAIL: sales@spectrawatermakers.com

www.spectrawatermakers.com