



Features & Benefits

Professional Series EV Advanced AGM Batteries, Designed and Engineered for Dependability in Commercial, Industrial, Public and Private applications; Mobility and Home Medical Equipment (HME) , Broadband and Cable TV (CATV), Uninterruptible Power Supplies (UPS) and Telecommunication, Photovoltaic, Solar and Renewable Energy, Electronic and Security, Marine and RV, Golf and Electric Vehicle, Aerial Lifts and Fork Lifts, Floor Machines and Robotics.

- *In Doors*
- *Out Back*
- *Off Shore*
- *On Duty*

Discover™ Professional Series Batteries have the Features and Benefits that matter to your customers and you!

Advanced AGM



- Completely sealed valve regulated construction.
- Flame arresting pressure regulated safety sealing valves for safety, operating pressure management and protection against atmospheric contamination (excess oxygen being absorbed by negative plates).
- Computer-aided 99.994% pure heavy-duty lead calcium grid designs.
- Tank formed plates: guarantees evenly formed and capacity matched plates.
- Discover™ proprietary Vision Max® Paste Formula.
- Anchored plate groups to guard against vibration.
- Double insulating Micro porous glass fiber separators.
- Measured and Immobilized electrolyte.
- Vacuum filling and weighing processes.
- Advanced technology for efficient gas recombination of up to 99.9% and freedom from electrolyte maintenance.
- Wide range of operating temperatures (-40°F to 140°F) (-60°F to 160°F Gel).
- Low self discharge rates (Approx. 1%-3% monthly at 68.F – 77.F)
- High impact reinforced strength copolymer polypropylene cases and flat top designed covers that are rugged and vibration resistant.
- Thermally welded case to cover bonds that eliminate leakage.
- Copper and stainless steel alloy terminals and hardware.
- Multi-terminal options.
- Terminal protectors.
- Removable carry handles.
- Industry leading size and performance options.
- Classified as “NON-SPILLABLE BATTERY” Not restricted for Air (IATA/ICAO) Provision 67, Surface (DOT-CFR-HMR49) or Water (Classified as non-hazardous per IMDG amendment 27) transportation
- Can be used in any orientation – Upside down is not recommended – do not charged up side down!
- Compatible with sensitive electronic equipment.
- Quality Assurance processes with ISO (4400/992579), QS and TUV Certification EMC tested, CE, ETTS Germany (G4M19906-9202-E-16)
- Tellcordia and Bellcore compliant
- UL recognized and approved components (MH29050).



EV12A-A

Mechanical Characteristics

Industry Type No.	Volts	Standard (optional) Terminals	Dimensions in Inches (mm)				Approx. Weight in Lbs (Kgs)
			L in(mm)	W in(mm)	H in(mm)	TH in(mm)	
EV12A	12	AM	12.88 (327)	6.93 (176)	10 (254)	10.8 (274)	89.5 (40.6)





Electrical Specifications

Ampere Hour Capacity			Minutes of Discharge					R/C	Cranking Amps	
20HR	10HR	5HR	@25A	@56A	@75A	@85A	@100A	@25A	32°F/ 0°C	0°F/ -18°C
* - Performance averages after 15 cycles										
140	133	119	335	98	71	61	45	310	1375	1100

Constant current discharge ratings-amperes at 20°C(77°F)

End Point volts/cell	10min	15min	30min	45min	1h	3h	5h	10h	20h
1.60V	286	224	135	100	86	35.6	24.4	13.5	7.0
1.65V	277	219	134	98	85	35.2	24.2	13.4	7.0
1.70V	268	214	132	97	84	34.7	24.0	13.4	6.9
1.75V	259	209	129	95	83	34.2	23.8	13.3	6.9
1.80V	250	204	125	93	82	33.7	23.6	13.3	6.8





Constant power discharge ratings-watts per cell at 20°C(77°F)

End Point volts/cell	10min	15min	30min	45min	1h	3h	5h	10h	20h
1.60V	507	393	262	194	152	69	46.2	24.3	12.7
1.65V	498	386	257	192	151	68	45.9	24.2	12.6
1.70V	488	380	251	190	150	67	45.6	24.1	12.5
1.75V	470	369	245	188	149	66	44.8	24.0	12.4
1.80V	451	354	238	185	148	65	43.8	23.9	12.3


Internal resistance	Fully charged at 20°C: 4.0 mOhms		
Self discharge	<3% of capacity per month at 20°C		
Operating temperature range	Discharge	Charge	Storage
	-20~60°C	-10~50°C	-20~60°C
Max. discharge current (20°C)	1000A(5s)		

CHARGE METHODS: Constant voltage charging at 20°C(68°F)			
	Max. Charge current	Charge voltage	Temperature compensation
Standby use	0.3C ₁₀ A	13.6—13.8V	-20mV/°C
Cyclic use	0.3C ₁₀ A	14.4--14.7V	-30mV/°C

Charge / Discharge Tables & Graphs



Relationship between charging voltage and temperature



Temperature effects on capacity

