



Ultralite

240 / 260 / 290

Designed and built to be light but tough and do all the things a tender should do best. Stable on water and a snack to get off the beach they are simply the best in this role.

Model	Length	Beam	Inside length	Inside width	Weight	Deadrise	Max pax	Max load	Max HP	Shaft	Tube Ø	Airtight chambers
UL 240	8	240cm 7' 10"	151cm 4' 11"	166cm 5' 5"	75cm 2' 5"	27kg 59lb	15°	3 290kg 639lb	4	Short	38cm 15"	3
UL 260	8.5	260cm 8' 6"	151cm 4' 11"	185cm 6' 1"	75cm 2' 5"	29kg 64lb	15°	4 375kg 827lb	6	Short	38cm 15"	3
UL 290	9.5	290cm 9' 6"	151cm 4' 11"	201cm 6' 7"	75cm 2' 5"	32kg 71lb	15°	4 420kg 926lb	8	short	38cm 15"	3

Standard equipment

- Valmex® PVC fabric from Mehler Technologies
- Welded seams
- Quality flush mount valves
- Craftsman built high tensile chromated & powder coated aluminium hull
- Removable rowing seat
- Lifting and towing eyes
- Towing bridles
- Non skid deck matting
- Light weight fender
- Keel guard
- Under seat bag
- Boat cover
- Highfield dry bag
- Pump, oars, repair kit

Optional equipment

- ORCA® Hypalon fabric from Pennel & Flipo
- Extra seat
- Dinghy wheels



Dinghy wheels



Boat cover



Under seat bag