



Maritime Series Watermakers

150 – 1600 GPD

Our Maritime Series Watermakers convert seawater to drinking water. Their compact design makes them ideal for use on yachts, boats, cruise ships, and resorts.



Key Features

- 30 years of experience is reflected in our quality
- Compact Powder Coated Aluminum Frame
- Proven components
- Engineered for reliable, long term performance
- Factory tested to ensure trouble-free operation

Standard Equipment

- Thin Film Composite Membranes
- FRP Membrane Housings
- Stainless Steel High Pressure Pump
- Permeate Flow Meter
- Low and High Pressure Shutoff Switches
- Compact Aluminum Frame with Powder Coated Finish
- Stainless Steel Back Pressure Control
- 5 Micron Sediment Filter and Housing
- Differential Gauge Showing Filter Life
- High Pressure Relief Valve
- Liquid Filled System Pressure Gauge
- Product TDS with Digital Display Readout
- Fresh Water Divert: Monitors Permeate Quality and diverts to drain if it falls below a pre-set set point
- Booster Pump and Raw Water Strainer
- Fresh Water Flush Module
- Installation Kit

Microprocessor Controller for Automatic Operation

Monitors and/or Controls:

- Booster Pump
- Delayed start-up of high pressure pump
- Low and high pressure switches
- On/Off with storage tank level*
- Permeate TDS with alarm set-point
- Water Temperature
- Operating Hours
- Fresh water flush
- Automatic product water diversion
- Pretreatment lock-out



Controller Features:

- Permeate Quality (TDS)
- Water Temperature
- Operating Hours
- Operating Status
- Alarm Condition
- NEMA 4X Enclosure
- Remote Control Operation (optional)

LED Display:

- Backlit LED Display
- Multi-function Keypad
- Visual and Audible Alarm
- Programmable Time Delays, Set-Points and Flush Modes
- Visual Indicator Alarm Light
- Low Pressure Automatic Restart

Model No.	System Capacity		Membrane Elements		Line Sizes (NPT, Inches)			System Dimensions (in/cm)			Approx. Shipping Weight (Lb/Kg)
	GPD	LPD	Qty.	Size (Dia. xL)	Inlet	Perm.	Conc.	Width	Depth	Height	
Maritime 150	150	567	1	2.5 x 21	3/4	1/4	1/2	24.5/53.3	19/48.3	12.5/31.6	110/50
Maritime 300	300	1135	2	2.5 x 21	3/4	1/4	1/2	24.5/53.3	19/48.3	12.5/31.6	115/52
Maritime 400	400	1514	1	2.5 x 40	3/4	3/8	1/2	43.5/110	23/58.4	15.75/40	130/60
Maritime 800	800	3028	2	2.5 x 40	3/4	3/8	1/2	43.5/110	23/58.4	15.75/40	140/65
Maritime 1200	1,200	4542	3	2.5 x 40	1	3/8	1/2	43.5/110	23/58.4	15.75/40	150/70
Maritime 1600	1,600	6056	4	2.5 x 40	1	3/8	1/2	43.5/110	23/58.4	15.75/40	180/80

Model No.	System Pressure		Power		Motor			Electrical			Fully Automated
	Normal PSI/BAR	Max PSI/BAR	kW	Amps	HP	FLA	Type	Voltage	Freq	Phase	
Maritime 150	700/48	1000/69	0.65	7/3.5	1	12.8	TEFC	115/240	50/60	1	yes
Maritime 300	800/55	1000/69	0.75	8.1/4	1	12.8	TEFC	115/240	50/60	1	yes
Maritime 400	700/48	1000/69	1.15	12.5/6.25	2.5	23/11.5	TEFC	115/240	50/60	1	yes
Maritime 800	750/52	1000/69	1.4	15.5/7.75	2.5	23/11.5	TEFC	115/240	50/60	1	yes
Maritime 1200	800/55	1000/69	1.5	16.5/8.25	2.5	23/11.5	TEFC	115/240	50/60	1	yes
Maritime 1600	800/55	1000/69	2.1	22/11	2.5	23/11.5	TEFC	115/240	50/60	1	yes

Notes and Voltage/ Ordering Information

- All dimensions and weights are approximate and subject to change. Performance Based on 32,000 ppm seawater at 77°F (25°C).
- * Requires the use of optional tank float switches
- **Voltage:** Please add our voltage codes to the end of the model number when ordering. Example: Maritime 150-236.
 - Voltage Codes:
 - **116** = 110v, 1ph, 60hz
 - **216** = 220/230v, 1ph, 60hz
 - **215** = 220/230v, 1ph, 50hz
 - **236** = 220 or 230v/ 3ph/ 60hz
 - **235** = 220v/3ph/50hz



Maritime Series Watermakers

150 – 1600 GPD

Options & Accessories

AMI's Watermakers are available with a wide variety of optional add-on accessories. All assemblies include hardware and mounting equipment for easy upgrade to your new or existing system installation.

Plankton Filter

Removes plankton and other large particles from the feed water to provide additional protection and extended life of the system prefilter. 100 Micron 10" Filter Cartridge in a clear housing on a powder coated mounting bracket. Includes isolation valves for easy cartridge change.



Model # A629

Remote Control

Connects to the main control board with a standard Cat5 cable, allowing you to start, stop, and monitor your watermaker from nearly anywhere. Designed for easy installation at a navigation station, galley, or pilothouse. Simple LED's show system status.



Model WMC-1-RMC

Oil Water Separator

Nothing fouls a membrane faster than oil. Protect your RO System & Membranes from oily or polluted water. 20" Filter Cartridge in a Big Blue housing on a powder coated mounting bracket. Includes isolation valves for easy cartridge change.



Model # A630

Membrane Preserving Cartridges

Pickling your system using AMI's exclusive preservative has never been simpler. Install this filter cartridge into your system and preserve the membranes in-place for extended periods of system shut-down. No more messing around with hoses, valves and plumbing connections.



Cartridge for 10" Std.: C-C2510-A88

Membrane Cleaning Cartridges

Just like membrane preservative cartridges shown above, but with chemicals designed to remove scale and bio-fouling from membranes. Clean membranes without removing them from your system, or altering valves, hoses or plumbing connections. Reduce downtime, maintain system performance, and prolong membrane life.



10" Std. (removes Scale): C-C2510-A11

10" Std. (removes organics): C-C2510-A22

Commercial Prefilter

The commercial sized filter cartridge has a dual-micron rating for extended life, and will provide longer intervals between changing the system prefilter. The outer layer will trap particles larger than 75 Micron, while the inner layer traps particles of 25 Micron. 20" Filter Cartridge in a Big Blue housing on a powder coated mounting bracket. Includes isolation valves for easy cartridge change.



Model A711

Media Filter

Removes suspended solids larger than 30 microns to greatly extend prefilter life and provide additional protection to the system. The 8x18" media tank is mounted on a powder coated frame with in/out pressure gauges and a valve for manual backwash. Multiple sizes available for higher flow rates.



Up to 3gpm: Model W-MB0818

Replacement Filters

We carry a large range of filters and housings manufactured under the AMI label. These high quality products use the same materials and produce similar performance specifications as the equivalent filters of other well-known brands.



Purchase Online:

www.appliedmembranes.com/filters

pH Neutralizer

Neutralizes the pH of the Fresh Water stream from the RO system. AMI calcite filters are self-limiting: they will correct pH only enough to reach a non-corrosive equilibrium, and will not over-correct. 10" Calcite Filter Cartridge in a blue housing on a powder coated mounting bracket. Includes isolation valves for easy cartridge change.

Model H-F251CALCITE

Ultraviolet (UV) System

Ultraviolet Water System for the fresh water stream to sterilize 99.8% of all micro-organisms including reproducing bacteria and viruses.



See our website for more information:

www.appliedmembranes.com/sq_series